

Steel drums**Open Head Drum – DN**

(210 litres)

**Drum for solid or liquid materials.**

The production and sales of container drums are the main activities of the Greif company in the field of packaging and services. The wide range of steel drums complies with strict regulations and requirements of petrochemical, chemical, pharmaceutical and food industry. Drums are manufactured with the latest technology and in accordance with the UN regulations for the transportation and storage of dangerous goods as well as with national and international legislation. This ensures optimum protection of a wide spectrum of packaged products, which meet the criteria for dangerous and non-dangerous goods.

- Drums are supplied in the configuration for solid or liquid materials.
- Protection of the external surface is ensured with environment-friendly water based paint that meets all legislative requirements.
- Drums can be delivered uncoated, with external coating in one or more colours, internally coated with special paint RDL® or they can be manufactured from double-side hot-dip galvanized steel sheets.
- All drum types can be supplied with a silk screen printed customer's logo.
- Drums with raw surface of the interior are suitable for packaging products that do not react with steel.
- Steel drums production complies with strict UN regulations for packing dangerous goods in the packaging groups I / X, II / Y, III / Z.
- In the version for liquids is the tightness of each drum checked with an automatic testing device. This guarantees the highest safety of the drums for transport and storage.

Standard Specification**Steel Sheets**

- Plain and coated drums are produced from steel sheets FeP01 produced in accordance to EN 10 130 and their properties comply with EN 10 131 and their national equivalents.
- Galvanized drums are produced from steel sheets DX51D+Z 140 produced in accordance to EN 10142: 1990/A:1995 and their properties comply with EN 10143:1993.

Closures

The drums can be supplied with a combination of Tri-Sure® 4S® G2" and G3/4" closures in the lid. Screw closures comply with the international standards of EN ISO 15750-3. Closures can be closed and sealed with Tab-Seal® caps in neutral or customer design. Closure flanges have standard sealing with a high-resistance system of 4S® sealing rings.

Construction

- **Body seam:**
Continuous resistance weld.
- **Standards:**
Drums are produced in accordance with EN ISO 15750-1.

Classification according to the type of transport


In compliance with the valid legislation and legislative executive regulations are drums of the Greif company production tested in accordance with the UN recommendations specified in Transports of dangerous goods – Model regulations and the sections of the International Collection for Transportation Chains as RID/ADR/IMDG – Code/ ICAO – IATA /ADN.



Steel drums
Open Head Drum – DN
(210 litres)




Drum dimensions



Beads/Corrugation

Type A



Type B



Body configuration

In the basic configuration, regardless of the thickness, drums are equipped with two rolling beads with diameter of 595 mm – type A.

2 x 3 additional corrugations enhance the body resistance against deformation by radial forces during shipment or manipulation – type B.

Bottom to body seaming

The seam is done with a safety double seaming Spiralon®.

Lid to body seaming

Drum lids are fixed with a closing ring with lever. Closing ring can be also secured with bolts and nuts. Drum lids for liquid materials are sealed with a sticking rubber sealing and fastened with a closing ring with reinforced construction.

UN Code marking

The UN code is embossed on the drum bottom and printed on the lower part of the drum body in accordance with international regulations.

Legislation

The products of Greif Czech Republic a.s. are supplied in accordance with the valid legislation.

Greif Czech Republic a.s.

Konečná 252

400 01 Ústí nad Labem

Czech Republic

VAT No.: CZ28708229

Telephone: +420 475 668 911, +420 475 668 941-2

Fax: +420 475 668 960, +420 475 668 962

e-mail: info.cz@greif.com

www.greif-cz.com